

XIS-1517

PRODUCT HIGHLIGHTS

320kV Generator

Picture Perfect Image Analysis

40 AWG Wire Resolution

Field Proven Reliability

80mm Steel Penetration



PRODUCT DESCRIPTION

4

0

The XIS-1517 320kV[™] is a powerful X-Ray Inspection System (XIS) designed for screening dense cargo. The system is equipped with an impressive 320kV generator capable of penetrating 80 mm of steel for high-quality imaging beyond competing machines with its tunnel size. The system's 320kV generator and field proven reliability ensures fortified security.

ABOUT ASTROPHYSICS

Since 2002, Astrophysics has led the industry in research and development, creating integrated solutions to advance the critical security missions of our customers and partners. Headquartered outside of Los Angeles, CA in the USA, Astrophysics has over 40,000 systems deployed in more than 150 countries, safeguarding critical infrastructure, aviation, and ports and border sites worldwide.

TOMORROW'S TECHNOLOGY FOR TODAY'S SECURITY™

XIS-1517[™]№

GENERAL SPECIFICATIONS

Tunnel Size: (WxH)	150.0 cm x 170.2 cm 59.0″ x 67.0″
Dimensions:1 (LxWxH)	948.7 cm x 280.0 cm x 229.9 cm 373.5" x 110.2" x 90.5"
Net Weight:1	11340 kg (25000 lbs)
Shipping Weight: ¹	13608 kg (30000 lbs)
Conveyor Speed:	20 cm/s (39 ft or 6m/min) Forward or Reverse
Conveyor Height:	38.3 cm (15") from Floor
Conveyor Capacity:	3000 kg (6613 lbs) Evenly Distributed Load

X-RAY GENERATOR & IMAGE PERFORMANCE

Voltage:	320kV
Tube Current:	7.0 mA
Wire Resolution: ²	40 AWG Typical, 38 AWG Standard
Steel Penetration: ²	80 mm Typical, 75 mm Standard
Duty Cycle:	100%, No Warm-Up Procedure Required
Beam Direction:	Horizontally Sideward
Detector:	2176 Channels in an L-Shaped Array

COMPUTER & VIDEO

Platform:Windows® OSDisplay Type:Dual 24" Flat Panel MonitorsDisplay Resolution:1920 x 1200Memory:8 GB RAMStorage Capacity:256 GB SSD

ENVIRONMENTAL

Operating Temperature: Storage Temperature: Humidity: 0°C to 40°C / 32°F to 104°F -20°C to 60°C / -4°F to 140°F Up to 95% Non-Condensing

ELECTRICAL

System Power: 110VAC +/- 10% 50/60Hz, 15 Amp Max 220 VAC +/- 10% 50/60Hz, 10 Amp Max Power Conditioner: Uninterruptible Power Supply (UPS)

(Computer Operation)

HEALTH & SAFETY

Compliant with USFDA Center for Devices and Radiation Health Standards for Cabinet X-Ray Systems (21-CFR 1020.40) Typical radiation leakage is less than 0.1 mR/hr (Leakage less than 0.5 mR/hr permitted by U.S. Federal Standards)

FEATURES

STANDARD

3 & 6 Color Imaging Black & White Imaging High Penetration Function Organic/Inorganic Imaging Picture Perfect Pseudo Color Reverse Monochrome

Atomic Z-Number Measurement Geometric Image Distortion Correction Material Discrimination Real-Time Image Manipulation

Auto Image Archiving Image Review Save Image (RGB)

Baggage Counter

Image Annotation JPEG Conversion Print Image Capable

Multi-Tier Accessibility Network Ready Real-Time Self Diagnostics

9 Quadrant Zoom Continuous Scanning Continuous Zoom Up to 64x Vertical Zoom Panning

OPTIONAL

Barcode Scanning Density Alert Local Language Safe Passage®Computer Based Training Screener Assist Software Test Case Threat Image Projection (TIP) Software

Conveyor Capacity Load Increase External USB Ports Variable Conveyor Speed

Custom Paint Entry/Exit Roller Tables Environmental Kit

Footmat Operator Interlock

Radiation Meter Remote Workstation Configuration





373.5 in



ARG

ISO 9001 & ISO 14001 CERTIFIED



¹Weight and dimensions of the system may vary depending on customization. ²As tested on Astrophysics Inc. Test Piece.

³Optional Features may affect lead time, price, and weight of product. Please contact your Astrophysics Sales Representative for more information.

Due to continued product development, Astrophysics Inc. reserves the right to amend all technical specifications without prior notice. Contact sales@astrophysicsinc.com for the most updated brochures.

Astrophysics HQ +1.909.598.5488 Astrophysics – EMEA +961.9.832.500 Astrophysics – INDIA +91.11.41709990 Astrophysics – ASIA +63.2.812.0033