

XIS-1517DV



PRODUCT DESCRIPTION

ABOUT ASTROPHYSICS

The XIS-1517DV[™] 200kV is a dual-view X-Ray Inspection System (XIS) designed for cargo screening. The system features a heavy duty roller bed only 38.3 cm (15") above the floor, convenient for loading and unloading freight. Its dual 200kV generators provide 52 mm of steel penetration and clear, highresolution images, making it an ideal solution for airports, logistics centers, and customs facilities. Since 2002, Astrophysics has led the industry in research and development, creating integrated solutions to advance the critical security missions of our customers and partners. Headquartered outside of Los Angeles, CA in the USA, Astrophysics has over 40,000 systems deployed in more than 150 countries, safeguarding critical infrastructure, aviation, and ports and border sites worldwide.

TOMORROW'S TECHNOLOGY FOR TODAY'S SECURITY™

XIS-1517DV

GENERAL SPECIFICATIONS

Tunnel Size: (WxH)	150.2 cm x 170.2 cm 59.1″ x 67.0″
Dimensions:1 (LxWxH)	853.1 cm x 259.1 cm x 286.3 cm 335.9" x 102.0" x 112.7"
Net Weight:1	5300 kg (11685 lbs)
Shipping Weight: ¹	5920.3 kg (13052 lbs)
Conveyor Speed:	20 cm/s (40 ft or 12m/min) Forward or Reverse
Conveyor Height:	38.3 cm (15.0") from Floor
Conveyor Capacity:	3000 kg (6613 lbs) Evenly Distributed Load

X-RAY GENERATOR & IMAGE PERFORMANCE

Voltage:	Dual 200kV
Tube Current:	Dual 1.0 mA
Wire Resolution: ²	40 AWG Typical, 38 AWG Standard
Steel Penetration: ²	52 mm Typical, 50 mm Standard
Cooling:	Sealed Di-Electric Oil Bath with Forced Air
Duty Cycle:	100%, No Warm Up Procedure Required
Beam Direction:	Horizontally Sideward, Vertically Downward

COMPUTER & VIDEO

Platform. Display Type: Display Resolution: Memory: Storage Capacity:

8 GB RAM 256 GB SSD **ENVIRONMENTAL**

Windows® 10 OS

1920 x 1200

Operating Temperature: Storage Temperature: Humidity:

0°C to 40°C / 32°F to 104°F -20°C to 60°C / -4°F to 140°F Up to 95% non-condensing

Dual 24" Flat Panel Monitors

ELECTRICAL

System Power:

Power Conditioner:

110VAC +/- 10% 50/60Hz, 20 Amp Max 220 VAC +/- 10% 50/60Hz, 15 Amp Max Uninterruptible Power Supply (UPS) (Computer Operation)

HEALTH & SAFETY

Compliant with USFDA Center for Devices and Radiation Health Standards for Cabinet X-Ray Systems (21-CFR 1020.40) Typical Radiation leakage is less than 0.1 mR/hr (Leakage less than 0.5 mR/hr permitted by U.S. Federal Standards)

FEATURES

STANDARD

3 & 6 Color Imaging Black & White Imaging Enhanced Imaging[™] Mode High Penetration Function Organic/Inorganic Imaging Pseudo Color Reverse Monochrome

Auto Image Archiving Image Review Save Image (RGB)

Atomic Z-Number Measurement Geometric Image Distortion Correction Material Discrimination Real-Time Image Manipulation

Baggage Counter

Image Annotation JPEG Conversion Print Image Capable

Multi-Tier Accessibility Network Ready Real-Time Self Diagnostics

9 Quadrant Zoom Continuous Scanning Continuous Zoom Up to 64x Vertical Zoom Panning

OPTIONAL

Barcode Scanning Density Alert Local Language Safe Passage® Computer Based Training Screener Assist Software Test Case Threat Image Projection (TIP) Software

Conveyor Capacity Load Increase External USB Ports Variable Conveyer Speed

Custom Paint Entry/Exit Roller Tables Environmental Kit

Footmat Operator Interlock

Radiation Meter Remote Workstation Configuration





ISO 9001 & ISO 14001 CERTIFIED



ANĨAB

²As tested on Astrophysics Inc. Test Piece.

³Optional Features may affect lead time, price, and weight of product. Please contact your Astrophysics Sales Representative for more information.

Due to continued product development, Astrophysics Inc. reserves the right to amend all technical specifications without prior notice. Contact sales@astrophysicsinc.com for the most updated brochures.

Astrophysics HQ +1.909.598.5488 Astrophysics – EMEA +961.9.832.500

Astrophysics – INDIA +91.11.41709990

Astrophysics – ASIA +63.2.812.0033

ARGO